








# Your new safety equipment requirements



## REQUIRED SAFETY EQUIPMENT

### Class 1E Passenger Vessels – 60 metres or longer

Sheltered Waters Passenger Vessel, 60 metres or longer, for use in Smooth waters only. (*Smooth water operations: operations within specified geographical limits designated 'Smooth waters'*)

 <p><b>Buoyant Appliances (general)</b></p>	<ul style="list-style-type: none"> <li>Any combination of buoyant appliances, lifebuoys and/or dinghies for 40% of allowable crew and any other persons on board, <u>subject to the following</u>:                             <ul style="list-style-type: none"> <li>Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less.</li> <li>Each lifebuoy is expected to provide support for 2 persons.</li> </ul> </li> <li>Vessels that do not conform to damaged stability requirements and single compartment subdivision shall be limited to a maximum of 49 Passengers and must carry buoyant appliances for 100% of allowable crew and any other persons on board.</li> <li>A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.</li> </ul>
 <p><b>Lifebuoys</b></p>	<ul style="list-style-type: none"> <li>6 x lifebuoys: 1 with a light; 1 with a buoyant line, 4 of operator's choice.                             <ul style="list-style-type: none"> <li>These lifebuoys are <u>in addition</u> to the Buoyant Appliances (general).</li> </ul> </li> </ul>
 <p><b>Life jackets</b></p>	<ul style="list-style-type: none"> <li>Coastal Life Jacket for 100% of allowable crew and any other persons on board.</li> </ul>
 <p><b>Distress signals</b></p>	<ul style="list-style-type: none"> <li>2 x Red hand-held flares.</li> <li>1 x Orange hand-held smoke flare.</li> </ul>
 <p><b>On-board communications and alarm systems</b></p>	<ul style="list-style-type: none"> <li>General emergency alarm system.</li> <li>Public address system (if no effective means of addressing passengers in time of emergency).</li> </ul>
 <p><b>Emergency lighting (hand-held)</b></p>	<ul style="list-style-type: none"> <li>1 x Battery operated torch for each crew member.</li> </ul>
 <p><b>Medical supplies</b></p>	<ul style="list-style-type: none"> <li>Annex H:                             <ul style="list-style-type: none"> <li><u>Berthed passengers</u> Scale F of Table H.3</li> <li><u>Unberthed</u> Scale G Table H.3                                     <ul style="list-style-type: none"> <li>The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only.</li> <li>Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.</li> </ul> </li> </ul> </li> </ul>








# Your new safety equipment requirements



## REQUIRED SAFETY EQUIPMENT

### Class 1E Passenger Vessels – Between 45 metres and less than 60 metres in length

Sheltered Waters Passenger Vessel, from 45 metres and less than 60 metres in length, for use in Smooth waters only. (*Smooth water operations: operations within specified geographical limits designated 'Smooth waters'*)

 <p><b>Buoyant Appliances (general)</b></p>	<ul style="list-style-type: none"> <li>Any combination of buoyant appliances, lifebuoys and/or dinghies for 40% of allowable crew and any other persons on board, <u>subject to the following</u>:                             <ul style="list-style-type: none"> <li>Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less.</li> <li>Each lifebuoy is expected to provide support for 2 persons.</li> </ul> </li> <li>Vessels that do not conform to damaged stability requirements and single compartment subdivision shall be limited to a maximum of 49 Passengers and must carry buoyant appliances for 100% of allowable crew and any other persons on board.</li> <li>A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.</li> </ul>
 <p><b>Lifebuoys</b></p>	<ul style="list-style-type: none"> <li>4 x Lifebuoys: 1 with a light; 1 with a buoyant line; 2 of operator's choice.                             <ul style="list-style-type: none"> <li>These lifebuoys are <u>in addition</u> to the Buoyant Appliances (general).</li> </ul> </li> </ul>
 <p><b>Life jackets</b></p>	<ul style="list-style-type: none"> <li>Coastal Life Jacket for 100% of allowable crew and any other persons on board.</li> </ul>
 <p><b>Distress signals</b></p>	<ul style="list-style-type: none"> <li>2 x Red hand-held flares.</li> <li>1 x Orange hand-held smoke flare.</li> </ul>
 <p><b>On-board communications and alarm systems</b></p>	<ul style="list-style-type: none"> <li>General emergency alarm system.</li> <li>Public address system (if no effective means of addressing passengers in time of emergency).</li> </ul>
 <p><b>Emergency lighting (hand-held)</b></p>	<ul style="list-style-type: none"> <li>1 x Battery operated torch for each crew member.</li> </ul>
 <p><b>Medical supplies</b></p>	<ul style="list-style-type: none"> <li>Annex H:                             <ul style="list-style-type: none"> <li><u>Berthed passengers</u> Scale F of Table H.3</li> <li><u>Unberthed</u> Scale G Table H.3                                     <ul style="list-style-type: none"> <li>The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only.</li> <li>Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.</li> </ul> </li> </ul> </li> </ul>










# Your new safety equipment requirements



## REQUIRED SAFETY EQUIPMENT

### Class 1E Passenger Vessels – Between 10 metres and less than 45 metres in length

Sheltered Waters Passenger Vessel, from 10 metres and less than 45 metres in length, for use in Smooth waters only. (*Smooth water operations: operations within specified geographical limits designated 'Smooth waters'*)

	<p><b>Buoyant Appliances (general)</b></p>	<ul style="list-style-type: none"> <li>Any combination of buoyant appliances, lifebuoys and/or dinghies for 40% of allowable crew and any other persons on board, <u>subject to the following</u>:                             <ul style="list-style-type: none"> <li>Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less.</li> <li>Each lifebuoy is expected to provide support for 2 persons.</li> </ul> </li> <li>Vessels that do not conform to damaged stability requirements and single compartment subdivision shall be limited to a maximum of 49 Passengers and must carry buoyant appliances for 100% of allowable crew and any other persons on board.</li> <li>A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.</li> <li>Vessels less than 25m must have suitable equipment to sustain and effectively recover persons overboard including: heaving line with rescue quoit, ladder, rescue sling, scramble net etc.</li> </ul>
	<p><b>Lifebuoys</b></p>	<ul style="list-style-type: none"> <li>2 x Lifebuoys: 1 with a light; 1 with a buoyant line.                             <ul style="list-style-type: none"> <li>These lifebuoys are <u>in addition</u> to Buoyant Appliances (general).</li> </ul> </li> </ul>
	<p><b>Life jackets</b></p>	<ul style="list-style-type: none"> <li>Coastal Life Jacket for 100% of allowable crew and any other persons on board.</li> </ul>
	<p><b>Distress signals</b></p>	<ul style="list-style-type: none"> <li>2 x Red hand-held flares.</li> <li>1 x Orange hand-held smoke flare.</li> </ul>
	<p><b>On-board communications and alarm systems</b></p>	<ul style="list-style-type: none"> <li>General emergency alarm system (For vessels 25m or longer).</li> <li>Public address system (if no effective means of addressing passengers in time of emergency).</li> </ul>
	<p><b>Emergency lighting (hand-held)</b></p>	<ul style="list-style-type: none"> <li>1 x Battery operated torch for each crew member.</li> </ul>
	<p><b>Medical supplies</b></p>	<ul style="list-style-type: none"> <li>Annex H:                             <ul style="list-style-type: none"> <li><u>Berthed passengers</u> Scale F of Table H.3</li> <li><u>Unberthed</u> Scale G Table H.3                                     <ul style="list-style-type: none"> <li>The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only.</li> <li>Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.</li> </ul> </li> </ul> </li> </ul>








# Your new safety equipment requirements



## REQUIRED SAFETY EQUIPMENT

### Class 1E Passenger Vessels – Less than 10 metres in length

Sheltered Waters Passenger Vessel, less than 10 metres in length, for use in Smooth waters only. (*Smooth water operations: operations within specified geographical limits designated 'Smooth waters'*)

 <p><b>Buoyant Appliances (general)</b></p>	<ul style="list-style-type: none"> <li>Any combination of buoyant appliances, lifebuoys and/or dinghies for 40% of allowable crew and any other persons on board, <u>subject to the following</u>:                             <ul style="list-style-type: none"> <li>Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less.</li> <li>Each lifebuoy is expected to provide support for 2 persons.</li> </ul> </li> <li>Vessels that do not conform to damaged stability requirements and single compartment subdivision shall be limited to a maximum of 49 Passengers and must carry buoyant appliances for 100% of allowable crew and any other persons on board.</li> <li>A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.</li> <li>Vessel must have suitable equipment to sustain and effectively recover persons overboard including: heaving line with rescue quoit, ladder, rescue sling, scramble net etc.</li> </ul>
 <p><b>Lifebuoys</b></p>	<ul style="list-style-type: none"> <li>1 x Lifebuoy with a light.                             <ul style="list-style-type: none"> <li>This lifebuoy is <u>in addition</u> to Buoyant Appliances (general).</li> </ul> </li> </ul>
 <p><b>Life jackets</b></p>	<ul style="list-style-type: none"> <li>Coastal Life Jacket for 100% of allowable crew and any other persons on board.</li> </ul>
 <p><b>Distress signals</b></p>	<ul style="list-style-type: none"> <li>2 x Red hand-held flares.</li> <li>1 x Orange hand-held smoke flare.</li> </ul>
 <p><b>On-board communications and alarm systems</b></p>	<ul style="list-style-type: none"> <li>Public address system (if no effective means of addressing passengers in time of emergency).</li> </ul>
 <p><b>Emergency lighting (hand-held)</b></p>	<ul style="list-style-type: none"> <li>1 x Battery operated torch for each crew member.</li> </ul>
 <p><b>Medical supplies</b></p>	<ul style="list-style-type: none"> <li>Annex H:                             <ul style="list-style-type: none"> <li>Berthed passengers Scale F of Table H.3</li> <li>Unberthed Scale G Table H.3                                     <ul style="list-style-type: none"> <li>The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only.</li> <li>Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.</li> </ul> </li> </ul> </li> </ul>