








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – 60 metres or longer

Sheltered Waters Passenger Vessel, 60 metres or longer, for use in Partially Smooth and Smooth waters only. (*Partially Smooth water operations: operations within specified geographical limits designated 'Partially Smooth waters' or 'Smooth waters'*)

 <p>Dinghy and Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> • A dinghy <u>plus</u> sufficient buoyant appliances and/or lifebuoys for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> – Open reversible Liferrafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. – Each lifebuoy is expected to provide support for 2 persons. – A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> • 8 x lifebuoys: 1 with a light; 1 with a buoyant line, 6 of operator's choice. <ul style="list-style-type: none"> – These lifebuoys are <u>in addition</u> to the buoyancy requirements (general).
 <p>Life jackets</p>	<ul style="list-style-type: none"> • Coastal Life Jacket for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> • 3 x Parachute distress rockets. • 2 x Red hand-held flares. • 1 x Orange hand-held smoke flare.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> • General emergency alarm system. • Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> • 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> • Annex H: <ul style="list-style-type: none"> – <u>Berthed passengers</u> Scale F of Table H.3 – <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> • The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. • Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – Between 45 metres and less than 60 metres in length

Sheltered Waters Passenger Vessel, from 45 metres and less than 60 metres in length, for use in Partially Smooth and Smooth Waters only. (*Partially Smooth water operations: operations within specified geographical limits designated 'Partially Smooth waters' or 'Smooth waters'*)

 <p>Dinghy and Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> • A dinghy <u>plus</u> sufficient buoyant appliances and/or lifebuoys for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> – Open reversible Liferrafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. – Each lifebuoy is expected to provide support for 2 persons. – A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> • 6 x lifebuoys: 1 with a light; 1 with a buoyant line, 4 of operator's choice. <ul style="list-style-type: none"> – These lifebuoys are <u>in addition</u> to the buoyancy requirements (general).
 <p>Life jackets</p>	<ul style="list-style-type: none"> • Coastal Life Jacket for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> • 3 x Parachute distress rockets. • 2 x Red hand-held flares. • 1 x Orange hand-held smoke flare.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> • General emergency alarm system. • Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> • 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> • Annex H: <ul style="list-style-type: none"> – <u>Berthed passengers</u> Scale F of Table H.3 – <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> • The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. • Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – Between 25 metres and less than 45 metres in length

Sheltered Waters Passenger Vessel, from 25 metres and less than 45 metres in length, for use in Partially Smooth and Smooth Waters only. (*Partially Smooth water operations: operations within specified geographical limits designated 'Partially Smooth waters' or 'Smooth waters'*)

 <p>Dinghy and Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> • A dinghy plus sufficient buoyant appliances and/or lifebuoys for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> – Open reversible Liferrafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. – Each lifebuoy is expected to provide support for 2 persons. – A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> • 4 x lifebuoys: 1 with a light; 1 with a buoyant line, 2 of operator's choice. <ul style="list-style-type: none"> – These lifebuoys are <u>in addition</u> to the Buoyancy requirements (general).
 <p>Life jackets</p>	<ul style="list-style-type: none"> • Coastal Life Jacket for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> • 3 x Parachute distress rockets. • 2 x Red hand-held flares. • 1 x Orange hand-held smoke flare.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> • General emergency alarm system. • Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> • 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> • Annex H: <ul style="list-style-type: none"> – <u>Berthed passengers</u> Scale F of Table H.3 – <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> • The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. • Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – Between 10 metres and less than 25 metres in length

Sheltered Waters Passenger Vessel, from 10 metres and less than 25 metres in length, for use in Partially Smooth and Smooth Waters only. (*Partially Smooth water operations: operations within specified geographical limits designated 'Partially Smooth waters' or 'Smooth waters'*)

	Buoyant Appliances (general)	<ul style="list-style-type: none"> Any combination of buoyant appliances, lifebuoys and/or dinghies for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. Each lifebuoy is expected to provide support for 2 persons. A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV. Vessel must have suitable equipment to sustain and effectively recover persons overboard including: heaving line with rescue quoit, ladder, rescue sling, scramble net etc.
	Lifebuoys	<ul style="list-style-type: none"> 2 x lifebuoys: 1 with a light, 1 with a buoyant line. <ul style="list-style-type: none"> These lifebuoys are <u>in addition</u> to Buoyancy requirements (general).
	Life jackets	<ul style="list-style-type: none"> Coastal Life Jacket for 100% of allowable crew and any other persons on board.
	Distress signals	<ul style="list-style-type: none"> 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flare.
	On-board communications and alarm systems	<ul style="list-style-type: none"> Public address system (if no effective means of addressing passengers in time of emergency).
	Emergency lighting (hand-held)	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
	Medical supplies	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> <u>Berthed passengers</u> Scale F of Table H.3 <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – Less than 10 metres in length

Sheltered Waters Passenger Vessel, less than 10 metres in length, for use in Partially Smooth and Smooth Waters only. (*Partially Smooth water operations: operations within specified geographical limits designated ‘Partially Smooth waters ’ or ‘Smooth waters’*)

	<p>Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> Any combination of buoyant appliances, lifebuoys and/or dinghies for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. Each lifebuoy is expected to provide support for 2 persons. A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV. Vessel must have suitable equipment to sustain and effectively recover persons overboard including: heaving line with rescue quoit, ladder, rescue sling, scramble net etc.
	<p>Lifebuoys</p>	<ul style="list-style-type: none"> 1 x Lifebuoy with a light. <ul style="list-style-type: none"> This lifebuoy is <u>in addition</u> to Buoyancy requirements (general).
	<p>Life jackets</p>	<ul style="list-style-type: none"> Coastal Life Jacket for 100% of allowable crew and any other persons on board.
	<p>Distress signals</p>	<ul style="list-style-type: none"> 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flare.
	<p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> Public address system (if no effective means of addressing passengers in time of emergency).
	<p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
	<p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> <u>Berthed passengers</u> Scale F of Table H.3 <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.