









Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1A Passenger Vessels – (any length)

Seagoing Commercial Passenger Vessel for use in Unlimited domestic operations.
(Unlimited domestic operations: all domestic operations up to and/or greater than 200 nautical miles to seaward of the coast.)

 Liferafts and rescue boats	<ul style="list-style-type: none"> • Marine Orders Part 25 applies.
 Buoyant appliances (general)	<ul style="list-style-type: none"> • Marine Orders Part 25 applies.
 Lifebuoys	<ul style="list-style-type: none"> • Marine Orders Part 25 applies.
 Life jackets	<ul style="list-style-type: none"> • Marine Orders Part 25 applies.
 Distress signals	<ul style="list-style-type: none"> • Marine Orders Part 25 applies.
 On-board communications and alarm systems	<ul style="list-style-type: none"> • Marine Orders Part 25 applies.
 Emergency lighting (hand-held)	<ul style="list-style-type: none"> • Marine Orders Part 25 applies.
 Medical supplies	<ul style="list-style-type: none"> • Marine Orders Part 10 applies.









Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1B Passenger Vessels – 60 metres or longer

Seagoing Passenger Vessel, 60 metres or longer, for use in all operational areas up to and including Offshore operations. (*Offshore Operations: operations within a limit of 200 nautical miles to seaward of the coast*)

 <p>Liferafts and rescue boats</p>	<ul style="list-style-type: none"> Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board <u>plus</u> a non-SOLAS Rescue Boat. <ul style="list-style-type: none"> Vessels continuously engaged on voyages in operational areas with a monthly mean temperature of 15° C or less must carry an anti-exposure suit for each person assigned to crew the Rescue Boat.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> 12 x Lifebuoys: 4 with a light; 2 with a light and smoke signal; 2 with a buoyant line; 4 of operator's choice.
 <p>Life jackets</p>	<ul style="list-style-type: none"> Adult SOLAS Life Jacket with a light for 100% of allowable crew and any other persons on board, plus a Child size SOLAS Life Jacket with a light for each passenger less than 32kg or 10% of the total vessel capacity which ever is the greater.
 <p>Distress signals</p>	<ul style="list-style-type: none"> 1 x 406MHz Electronic Position Indicating Radio Beacon. 6 x Parachute distress rockets. 4 x Red hand-held flares. 2 x Orange hand-held smoke flares.
 <p>Line Throwing Appliance</p>	<ul style="list-style-type: none"> 4 x Rockets and lines.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> General emergency alarm system. Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 2 x Battery operated torches.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: Scale D of Tables H.4 and H.5 and Scale F of Table H.3. <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.









Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1B Passenger Vessels – Between 45 metres and less than 60 metres in length

Seagoing Passenger Vessel, from 45 metres and less than 60 metres in length, for use in all operational areas up to and including Offshore operations. (*Offshore Operations: operations within a limit of 200 nautical miles to seaward of the coast*)

 <p>Liferafts and rescue boats</p>	<ul style="list-style-type: none"> Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board <u>plus</u> a non-SOLAS Rescue Boat. <ul style="list-style-type: none"> Vessels continuously engaged on voyages in operational areas with a monthly mean temperature of 15° C or less must carry an anti-exposure suit for each person assigned to crew the Rescue Boat.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> 8 x Lifebuoys: 2 with a light; 2 with a light and smoke signal; 2 with a buoyant line; 2 of operator's choice.
 <p>Life jackets</p>	<ul style="list-style-type: none"> Adult SOLAS Life Jacket with a light for 100% of allowable crew and any other persons on board, plus a Child size SOLAS Life Jacket with a light for each passenger less than 32kg or 10% of the total vessel capacity which ever is the greater.
 <p>Distress signals</p>	<ul style="list-style-type: none"> 1 x 406MHz Electronic Position Indicating Radio Beacon. 6 x Parachute distress rockets. 4 x Red hand-held flares. 2 x Orange hand-held smoke flares.
 <p>Line Throwing Appliance</p>	<ul style="list-style-type: none"> 4 x Rockets and lines.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> General emergency alarm system. Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 2 x Battery operated torches.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: Scale D of Tables H.4 and H.5 and Scale F of Table H.3. <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1B Passenger Vessels – Between 25 metres and less than 45 metres in length

Seagoing Passenger Vessel, from 25 metres and less than 45 metres in length, for use in all operational areas up to and including Offshore operations. (*Offshore Operations: operations within a limit of 200 nautical miles to seaward of the coast*)

 <p>Liferafts and rescue boats</p>	<ul style="list-style-type: none"> Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board plus a non-SOLAS Rescue Boat. <ul style="list-style-type: none"> Vessels continuously engaged on voyages in operational areas with a monthly mean temperature of 15° C or less must carry an anti-exposure suit for each person assigned to crew the Rescue Boat.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> 6 x Lifebuoys: 1 with a light; 2 with a light and smoke signal, 2 with a buoyant lines and 1 of operators choice.
 <p>Life jackets</p>	<ul style="list-style-type: none"> Adult SOLAS Life Jacket with a light for 100% of allowable crew and any other persons on board, plus a Child size SOLAS Life Jacket with a light for each passenger less than 32kg or 10% of the total vessel capacity which ever is the greater.
 <p>Distress signals</p>	<ul style="list-style-type: none"> 1 x 406MHz Electronic Position Indicating Radio Beacon. 6 x Parachute distress rockets. 4 x Red hand-held flares. 2 x Orange hand-held smoke flares.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> General emergency alarm system. Public address system (if no effective means of addressing passengers in time of emergency)
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 2 x Battery operated torches.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: Scale D of Tables H.4 and H.5 and Scale F of Table H.3. <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1B Passenger Vessels – Between 10 metres and less than 25 metres in length

Seagoing Passenger Vessel, from 10 metres and less than 25 metres in length, for use in all operational areas up to and including Offshore operations. (*Offshore Operations: operations within a limit of 200 nautical miles to seaward of the coast*)

 Liferafts	<ul style="list-style-type: none"> • Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board.
 Lifebuoys	<ul style="list-style-type: none"> • 2 x lifebuoys: 1 with a light; 1 with a buoyant line.
 Life jackets	<ul style="list-style-type: none"> • Adult SOLAS Life Jacket with a light for 100% of allowable crew and any other persons on board, plus a Child size SOLAS Life Jacket with a light for each passenger less than 32kg or 10% of the total vessel capacity which ever is the greater.
 Distress signals	<ul style="list-style-type: none"> • 1 x 406MHz Electronic Position Indicating Radio Beacon. • 6 x Parachute distress rockets. • 4 x Red hand-held flares. • 2 x Orange hand-held smoke flares.
 On-board communications and alarm systems	<ul style="list-style-type: none"> • Public address system (if no effective means of addressing passengers in time of emergency).
 Emergency lighting (hand-held)	<ul style="list-style-type: none"> • 2 x Battery operated torches.
 Medical supplies	<ul style="list-style-type: none"> • Annex H: Scale D of Tables H.4 and H.5 and Scale F of Table H.3. <ul style="list-style-type: none"> – The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. – Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.







Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1B Passenger Vessels – Less than 10 metres in length

Seagoing Passenger Vessel, less than 10 metres in length, for use in all operational areas up to and including Offshore operations. (*Offshore Operations: operations within a limit of 200 nautical miles to seaward of the coast*)

 <p>Liferafts</p>	<ul style="list-style-type: none"> • Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board.
 <p>Life jackets</p>	<ul style="list-style-type: none"> • Adult SOLAS Life Jacket with a light for 100% of allowable crew and any other persons on board, plus a Child size SOLAS Life Jacket with a light for each passenger less than 32kg or 10% of the total vessel capacity which ever is the greater.
 <p>Distress signals</p>	<ul style="list-style-type: none"> • 1 x 406MHz Electronic Position Indicating Radio Beacon. • 6 x Parachute distress rockets. • 4 x Red hand-held flares. • 2 x Orange hand-held smoke flares.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> • Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> • 2 x Battery operated torches.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> • Annex H: Scale D of Tables H.4 and H.5 and Scale F of Table H.3. <ul style="list-style-type: none"> – The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. – Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.











Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1C Passenger Vessels – 60 metres or longer

Seagoing Passenger Vessel, 60 metres or longer, for use in all operational areas up to and including Restricted offshore operations. (*Restricted offshore operations: operations within a limit of 50 nautical miles seaward from designated smooth or partially smooth waters, designated restricted offshore waters or a safe haven*)

 <p>Liferafts and rescue boats</p>	<ul style="list-style-type: none"> Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board <u>plus</u> a non-SOLAS Rescue Boat. <ul style="list-style-type: none"> Vessels continuously engaged on voyages in operational areas with a monthly mean temperature of 15° C or less must carry an anti-exposure suit for each person assigned to crew the Rescue Boat.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> 8 x Lifebuoys: 2 with lights; 2 with a light and smoke signal; 2 with a buoyant line; 2 of operator's choice.
 <p>Life jackets</p>	<ul style="list-style-type: none"> Coastal Life Jacket with a light for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> 1 x 406MHz Electronic Position Indicating Radio Beacon. 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flares.
 <p>Line Throwing Appliance</p>	<ul style="list-style-type: none"> 4 x Rockets and lines.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> General emergency alarm system. Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> <u>Berthed passengers</u> Scale E of Tables H.4 and H.5 and Scale F of Table H.3 <u>Unberthed</u> Scale F of Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.









Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1C Passenger Vessels – Between 45 metres and less than 60 metres in length

Seagoing Passenger Vessel, from 45 metres and less than 60 metres in length, for use in all operational areas up to and including Restricted offshore operations. (*Restricted offshore operations: operations within a limit of 50 nautical miles seaward from designated smooth, partially smooth or restricted offshore waters or a safe haven*)

 <p>Liferafts and rescue boats</p>	<ul style="list-style-type: none"> Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board <u>plus</u> a non-SOLAS Rescue Boat. <ul style="list-style-type: none"> Vessels continuously engaged on voyages in operational areas with a monthly mean temperature of 15° C or less must carry an anti-exposure suit for each person assigned to crew the Rescue Boat.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> 6 x Lifebuoys: 1 with a light; 2 with a light and a smoke signal; 2 with a buoyant line; 1 of operator's choice.
 <p>Life jackets</p>	<ul style="list-style-type: none"> Coastal Life Jacket with a light for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> 1 x 406MHz Electronic Position Indicating Radio Beacon. 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flares.
 <p>Line Throwing Appliance</p>	<ul style="list-style-type: none"> 4 x Rockets and lines.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> General emergency alarm system. Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> Berthed passengers Scale E of Tables H.4 and H.5 and Scale F of Table H.3 Unberthed Scale F of Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1C Passenger Vessels – Between 25 metres and less than 45 metres in length

Seagoing Passenger Vessel, from 25 metres and less than 45 metres in length, for use in all operational areas up to and including Restricted offshore operations. (*Restricted offshore operations: operations within a limit of 50 nautical miles seaward from designated smooth or partially smooth waters, designated restricted offshore waters or a safe haven*)

 <p>Liferafts and rescue boats</p>	<ul style="list-style-type: none"> Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board plus a non-SOLAS Rescue Boat. <ul style="list-style-type: none"> Vessels continuously engaged on voyages in operational areas with a monthly mean temperature of 15° C or less must carry an anti-exposure suit for each person assigned to crew the Rescue Boat.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> 4 x Lifebuoys: 2 with a light and a smoke signal; 2 with a buoyant line.
 <p>Life jackets</p>	<ul style="list-style-type: none"> Coastal Life Jacket with a light for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> 1 x 406MHz Electronic Position Indicating Radio Beacon. 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flares.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> General emergency alarm system. Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> Berthed passengers Scale E of Tables H.4 and H.5 and Scale F of Table H.3 Unberthed Scale F of Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1C Passenger Vessels – Between 10 metres and less than 25 metres in length

Seagoing Passenger Vessel, from 10 metres and less than 25 metres in length, for use in all operational areas up to and including Restricted offshore operations. (*Restricted offshore operations: operations within a limit of 50 nautical miles seaward from designated smooth or partially smooth waters, designated restricted offshore waters or a safe haven*)

 Liferafts	<ul style="list-style-type: none"> Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board.
 Lifebuoys	<ul style="list-style-type: none"> 2 x lifebuoys: 1 with a light; 1 with a buoyant line.
 Life jackets	<ul style="list-style-type: none"> Coastal Life Jacket with light for 100% of allowable crew and any other persons on board.
 Distress signals	<ul style="list-style-type: none"> 1 x 406MHz Electronic Position Indicating Radio Beacon. 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flares.
 On-board communications and alarm systems	<ul style="list-style-type: none"> Public address system (if no effective means of addressing passengers in time of emergency).
 Emergency lighting (hand-held)	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
 Medical supplies	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> Berthed passengers Scale E of Tables H.4 and H.5 and Scale F of Table H.3 Unberthed Scale F of Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.







Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1C Passenger Vessels – Less than 10 metres in length

Seagoing Passenger Vessel, less than 10 metres in length, for use in all operational areas up to and including Restricted offshore operations. (*Restricted offshore operations: operations within a limit of 50 nautical miles seaward from designated smooth or partially smooth waters, designated restricted offshore waters or a safe haven*)

 Liferafts	<ul style="list-style-type: none"> Inflatable Coastal Liferaft(s) for 100% of allowable crew and any other persons on board.
 Life jackets	<ul style="list-style-type: none"> Coastal Life Jacket with a light for 100% of allowable crew and any other persons on board.
 Distress signals	<ul style="list-style-type: none"> 1 x 406MHz Electronic Position Indicating Radio Beacon. 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flares.
 On-board communications and alarm systems	<ul style="list-style-type: none"> Public address system (if no effective means of addressing passengers in time of emergency).
 Emergency lighting (hand-held)	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
 Medical supplies	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> Berthed passengers Scale E of Tables H.4 and H.5 and Scale F of Table H.3 Unberthed Scale F of Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.










Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – 60 metres or longer

Sheltered Waters Passenger Vessel, 60 metres or longer, for use in Partially Smooth and Smooth waters only. (*Partially Smooth water operations: operations within specified geographical limits designated 'Partially Smooth waters' or 'Smooth waters'*)

 <p>Dinghy and Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> • A dinghy <u>plus</u> sufficient buoyant appliances and/or lifebuoys for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> – Open reversible Liferrafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. – Each lifebuoy is expected to provide support for 2 persons. – A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> • 8 x lifebuoys: 1 with a light; 1 with a buoyant line, 6 of operator's choice. <ul style="list-style-type: none"> – These lifebuoys are <u>in addition</u> to the buoyancy requirements (general).
 <p>Life jackets</p>	<ul style="list-style-type: none"> • Coastal Life Jacket for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> • 3 x Parachute distress rockets. • 2 x Red hand-held flares. • 1 x Orange hand-held smoke flare.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> • General emergency alarm system. • Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> • 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> • Annex H: <ul style="list-style-type: none"> – <u>Berthed passengers</u> Scale F of Table H.3 – <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> • The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. • Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – Between 45 metres and less than 60 metres in length

Sheltered Waters Passenger Vessel, from 45 metres and less than 60 metres in length, for use in Partially Smooth and Smooth Waters only. (*Partially Smooth water operations: operations within specified geographical limits designated 'Partially Smooth waters' or 'Smooth waters'*)

 <p>Dinghy and Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> • A dinghy <u>plus</u> sufficient buoyant appliances and/or lifebuoys for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> – Open reversible Liferrafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. – Each lifebuoy is expected to provide support for 2 persons. – A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> • 6 x lifebuoys: 1 with a light; 1 with a buoyant line, 4 of operator's choice. <ul style="list-style-type: none"> – These lifebuoys are <u>in addition</u> to the buoyancy requirements (general).
 <p>Life jackets</p>	<ul style="list-style-type: none"> • Coastal Life Jacket for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> • 3 x Parachute distress rockets. • 2 x Red hand-held flares. • 1 x Orange hand-held smoke flare.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> • General emergency alarm system. • Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> • 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> • Annex H: <ul style="list-style-type: none"> – <u>Berthed passengers</u> Scale F of Table H.3 – <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> • The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. • Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – Between 25 metres and less than 45 metres in length

Sheltered Waters Passenger Vessel, from 25 metres and less than 45 metres in length, for use in Partially Smooth and Smooth Waters only. (*Partially Smooth water operations: operations within specified geographical limits designated 'Partially Smooth waters' or 'Smooth waters'*)

 <p>Dinghy and Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> • A dinghy <u>plus</u> sufficient buoyant appliances and/or lifebuoys for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> – Open reversible Liferrafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. – Each lifebuoy is expected to provide support for 2 persons. – A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> • 4 x lifebuoys: 1 with a light; 1 with a buoyant line, 2 of operator's choice. <ul style="list-style-type: none"> – These lifebuoys are <u>in addition</u> to the Buoyancy requirements (general).
 <p>Life jackets</p>	<ul style="list-style-type: none"> • Coastal Life Jacket for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> • 3 x Parachute distress rockets. • 2 x Red hand-held flares. • 1 x Orange hand-held smoke flare.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> • General emergency alarm system. • Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> • 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> • Annex H: <ul style="list-style-type: none"> – <u>Berthed passengers</u> Scale F of Table H.3 – <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> • The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. • Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – Between 10 metres and less than 25 metres in length

Sheltered Waters Passenger Vessel, from 10 metres and less than 25 metres in length, for use in Partially Smooth and Smooth Waters only. (*Partially Smooth water operations: operations within specified geographical limits designated 'Partially Smooth waters' or 'Smooth waters'*)

	Buoyant Appliances (general)	<ul style="list-style-type: none"> Any combination of buoyant appliances, lifebuoys and/or dinghies for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. Each lifebuoy is expected to provide support for 2 persons. A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV. Vessel must have suitable equipment to sustain and effectively recover persons overboard including: heaving line with rescue quoit, ladder, rescue sling, scramble net etc.
	Lifebuoys	<ul style="list-style-type: none"> 2 x lifebuoys: 1 with a light, 1 with a buoyant line. <ul style="list-style-type: none"> These lifebuoys are <u>in addition</u> to Buoyancy requirements (general).
	Life jackets	<ul style="list-style-type: none"> Coastal Life Jacket for 100% of allowable crew and any other persons on board.
	Distress signals	<ul style="list-style-type: none"> 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flare.
	On-board communications and alarm systems	<ul style="list-style-type: none"> Public address system (if no effective means of addressing passengers in time of emergency).
	Emergency lighting (hand-held)	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
	Medical supplies	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> <u>Berthed passengers</u> Scale F of Table H.3 <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1D Passenger Vessels – Less than 10 metres in length

Sheltered Waters Passenger Vessel, less than 10 metres in length, for use in Partially Smooth and Smooth Waters only. (*Partially Smooth water operations: operations within specified geographical limits designated ‘Partially Smooth waters ’ or ‘Smooth waters’*)

	<p>Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> Any combination of buoyant appliances, lifebuoys and/or dinghies for 100% of allowable crew and any other persons on board. <ul style="list-style-type: none"> Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. Each lifebuoy is expected to provide support for 2 persons. A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV. Vessel must have suitable equipment to sustain and effectively recover persons overboard including: heaving line with rescue quoit, ladder, rescue sling, scramble net etc.
	<p>Lifebuoys</p>	<ul style="list-style-type: none"> 1 x Lifebuoy with a light. <ul style="list-style-type: none"> This lifebuoy is <u>in addition</u> to Buoyancy requirements (general).
	<p>Life jackets</p>	<ul style="list-style-type: none"> Coastal Life Jacket for 100% of allowable crew and any other persons on board.
	<p>Distress signals</p>	<ul style="list-style-type: none"> 3 x Parachute distress rockets. 2 x Red hand-held flares. 1 x Orange hand-held smoke flare.
	<p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> Public address system (if no effective means of addressing passengers in time of emergency).
	<p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
	<p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> <u>Berthed passengers</u> Scale F of Table H.3 <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.










Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1E Passenger Vessels – 60 metres or longer

Sheltered Waters Passenger Vessel, 60 metres or longer, for use in Smooth waters only. (*Smooth water operations: operations within specified geographical limits designated ‘Smooth waters’*)

 <p>Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> Any combination of buoyant appliances, lifebuoys and/or dinghies for 40% of allowable crew and any other persons on board, <u>subject to the following</u>: <ul style="list-style-type: none"> Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. Each lifebuoy is expected to provide support for 2 persons. Vessels that do not conform to damaged stability requirements and single compartment subdivision shall be limited to a maximum of 49 Passengers and must carry buoyant appliances for 100% of allowable crew and any other persons on board. A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.
 <p>Lifebuoys</p>	<ul style="list-style-type: none"> 6 x lifebuoys: 1 with a light; 1 with a buoyant line, 4 of operator’s choice. <ul style="list-style-type: none"> These lifebuoys are <u>in addition</u> to the Buoyant Appliances (general).
 <p>Life jackets</p>	<ul style="list-style-type: none"> Coastal Life Jacket for 100% of allowable crew and any other persons on board.
 <p>Distress signals</p>	<ul style="list-style-type: none"> 2 x Red hand-held flares. 1 x Orange hand-held smoke flare.
 <p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> General emergency alarm system. Public address system (if no effective means of addressing passengers in time of emergency).
 <p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
 <p>Medical supplies</p>	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> <u>Berthed passengers</u> Scale F of Table H.3 <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1E Passenger Vessels – Between 45 metres and less than 60 metres in length

Sheltered Waters Passenger Vessel, from 45 metres and less than 60 metres in length, for use in Smooth waters only. (*Smooth water operations: operations within specified geographical limits designated 'Smooth waters'*)

	Buoyant Appliances (general)	<ul style="list-style-type: none"> Any combination of buoyant appliances, lifebuoys and/or dinghies for 40% of allowable crew and any other persons on board, subject to the following: <ul style="list-style-type: none"> Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. Each lifebuoy is expected to provide support for 2 persons. Vessels that do not conform to damaged stability requirements and single compartment subdivision shall be limited to a maximum of 49 Passengers and must carry buoyant appliances for 100% of allowable crew and any other persons on board. A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV.
	Lifebuoys	<ul style="list-style-type: none"> 4 x Lifebuoys: 1 with a light; 1 with a buoyant line; 2 of operator's choice. <ul style="list-style-type: none"> These lifebuoys are <u>in addition</u> to the Buoyant Appliances (general).
	Life jackets	<ul style="list-style-type: none"> Coastal Life Jacket for 100% of allowable crew and any other persons on board.
	Distress signals	<ul style="list-style-type: none"> 2 x Red hand-held flares. 1 x Orange hand-held smoke flare.
	On-board communications and alarm systems	<ul style="list-style-type: none"> General emergency alarm system. Public address system (if no effective means of addressing passengers in time of emergency).
	Emergency lighting (hand-held)	<ul style="list-style-type: none"> 1 x Battery operated torch for each crew member.
	Medical supplies	<ul style="list-style-type: none"> Annex H: <ul style="list-style-type: none"> Berthed passengers Scale F of Table H.3 Unberthed Scale G Table H.3 <ul style="list-style-type: none"> The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.










Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1E Passenger Vessels – Between 10 metres and less than 45 metres in length

Sheltered Waters Passenger Vessel, from 10 metres and less than 45 metres in length, for use in Smooth waters only. (*Smooth water operations: operations within specified geographical limits designated 'Smooth waters'*)

	Buoyant Appliances (general)	<ul style="list-style-type: none"> • Any combination of buoyant appliances, lifebuoys and/or dinghies for 40% of allowable crew and any other persons on board, subject to the following: <ul style="list-style-type: none"> – Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. – Each lifebuoy is expected to provide support for 2 persons. • Vessels that do not conform to damaged stability requirements and single compartment subdivision shall be limited to a maximum of 49 Passengers and must carry buoyant appliances for 100% of allowable crew and any other persons on board. • A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV. • Vessels less than 25m must have suitable equipment to sustain and effectively recover persons overboard including: heaving line with rescue quoit, ladder, rescue sling, scramble net etc.
	Lifebuoys	<ul style="list-style-type: none"> • 2 x Lifebuoys: 1 with a light; 1 with a buoyant line. <ul style="list-style-type: none"> – These lifebuoys are <u>in addition</u> to Buoyant Appliances (general).
	Life jackets	<ul style="list-style-type: none"> • Coastal Life Jacket for 100% of allowable crew and any other persons on board.
	Distress signals	<ul style="list-style-type: none"> • 2 x Red hand-held flares. • 1 x Orange hand-held smoke flare.
	On-board communications and alarm systems	<ul style="list-style-type: none"> • General emergency alarm system (For vessels 25m or longer). • Public address system (if no effective means of addressing passengers in time of emergency).
	Emergency lighting (hand-held)	<ul style="list-style-type: none"> • 1 x Battery operated torch for each crew member.
	Medical supplies	<ul style="list-style-type: none"> • Annex H: <ul style="list-style-type: none"> – <u>Berthed passengers</u> Scale F of Table H.3 – <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> • The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. • Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.








Your new safety equipment requirements



REQUIRED SAFETY EQUIPMENT

Class 1E Passenger Vessels – Less than 10 metres in length

Sheltered Waters Passenger Vessel, less than 10 metres in length, for use in Smooth waters only. (*Smooth water operations: operations within specified geographical limits designated 'Smooth waters'*)

	<p>Buoyant Appliances (general)</p>	<ul style="list-style-type: none"> • Any combination of buoyant appliances, lifebuoys and/or dinghies for 40% of allowable crew and any other persons on board, <u>subject to the following</u>: <ul style="list-style-type: none"> – Open reversible life rafts must be used in place of buoyant appliances if the vessel is engaged on voyages in operational areas with a monthly mean temperature of 15°C or less. – Each lifebuoy is expected to provide support for 2 persons. • Vessels that do not conform to damaged stability requirements and single compartment subdivision shall be limited to a maximum of 49 Passengers and must carry buoyant appliances for 100% of allowable crew and any other persons on board. • A reduction in buoyant appliance capacity may be allowable in accordance with Part B of the NSCV. • Vessel must have suitable equipment to sustain and effectively recover persons overboard including: heaving line with rescue quoit, ladder, rescue sling, scramble net etc.
	<p>Lifebuoys</p>	<ul style="list-style-type: none"> • 1 x Lifebuoy with a light. <ul style="list-style-type: none"> – This lifebuoy is <u>in addition</u> to Buoyant Appliances (general).
	<p>Life jackets</p>	<ul style="list-style-type: none"> • Coastal Life Jacket for 100% of allowable crew and any other persons on board.
	<p>Distress signals</p>	<ul style="list-style-type: none"> • 2 x Red hand-held flares. • 1 x Orange hand-held smoke flare.
	<p>On-board communications and alarm systems</p>	<ul style="list-style-type: none"> • Public address system (if no effective means of addressing passengers in time of emergency).
	<p>Emergency lighting (hand-held)</p>	<ul style="list-style-type: none"> • 1 x Battery operated torch for each crew member.
	<p>Medical supplies</p>	<ul style="list-style-type: none"> • Annex H: <ul style="list-style-type: none"> – <u>Berthed</u> passengers Scale F of Table H.3 – <u>Unberthed</u> Scale G Table H.3 <ul style="list-style-type: none"> • The quantity of medical supplies identified in Annex H is based on incidents involving 1 or 2 persons only. • Medical supplies will need to be expanded in accordance with the particular risks inherent to the voyage and the number of persons on board.