Marine information Bulletin

Safety equipment and registration requirements for tenders to Queensland regulated ships

September 2016

Purpose

This Marine Information Bulletin clarifies safety equipment and registration requirements for tenders to Queensland regulated ships.

What is a tender?

A tender is a boat that is not a lifeboat, is 6m or less in length and is smaller than the parent ship.

It can only be used to transport people or provisions between the ship and shore or ship to ship.

Registration

Tenders to Queensland regulated ships are exempt from registration if they are only used within 2 nautical miles (nm) of the parent ship.

Refer to Table 1 for more information.

Safety equipment

A tender that is required to be registered must carry lifejackets and other safety equipment stipulated under the *Transport Operations (Marine Safety) Regulation* 2016.

Table 2 is a list of safety equipment to be carried on board the tender.

Emergency Position Indicating Radio Beacon (EPIRB)

All tenders operating between sunset and sunrise must be equipped with navigation lights and a lighting device for signalling to attract attention.

Recommended miscellaneous equipment

It is recommended that all tenders carry the miscellaneous equipment outlined in Table 2 to meet their general safety obligation.

Compliance with the general safety obligation

Operators of all boats including tenders are required to comply with the general safety obligation as per the *Transport Operations (Marine Safety) Act 1994.*

The owner/master of a boat must not operate the boat unless the boat is safe. A boat is safe if it is seaworthy, and is appropriately equipped and crewed for the voyage.

Further information

For further information contact your local Maritime Safety Queensland office:

| Airlie Beach | 4841 4500 |
|--------------|-----------|
| Bundaberg | 4132 6600 |
| Cairns | 4052 7400 |
| Gladstone | 4971 5200 |
| Hervey Bay | 4194 9600 |
| Mackay | 4944 3700 |
| Mooloolaba | 5452 1825 |
| Brisbane | 3632 7500 |
| Gold Coast | 5585 1810 |
| Townsville | 4421 8100 |

Other Marine Information Bulletins about the safe operation of boats are on Maritime Safety Queensland's website: www.msq.qld.gov.au



Table 1 – Registration requirements for 6m or less tenders to Queensland regulated ships

| Engine Power | Operating radius from parent ship | Requires registration? |
|----------------|--|------------------------|
| less than 3 kW | any distance | NO |
| 3 kW or more | less than 2 nautical miles* (nm) (3.7km) | NO |
| | 2nm (3.7km) or more | YES |

^{*}The tender must be marked on the exterior with the word 'tender' and the parent ship registration number, at least 75mm high.

Table 2 – safety and miscellaneous equipment for tenders to Queensland regulated ships

| Item | Smooth Waters | | Partially smooth waters | | Beyond partially smooth waters | |
|---|--|--|--------------------------|--|--------------------------------|-------------------------------|
| | Requires Registration | Not requiring Registration | Requires Registration | Not requiring Registration | Requires Registration | Not requiring Registration |
| Lifejacket for each | Required | Recommended | Required | Recommended | Required | Recommended |
| person on board | At least 'Level 50S (special purpose)' | At least 'Level 50S (special purpose)' | At least 'Level 50' | At least 'Level 50' | At least 'Level 100' | At least 'Level 100' |
| | Not required when the tender has a positive flotation statement and is operating either: Within 1km of the parent ship In a river, creek, stream, or the waters contained within breakwater or revetments and is equipped with grab lines, grab rails, or other permanent means of giving each person on board a way of keeping a secure hold to the tender. | | | Not required when the tender has a positive flotation statement and is operating within 500m of the parent ship. | | |
| Signalling device | Required | Required | Required | Required | Required | Required |
| when operating between sunset and sunrise | for example, a torch, I | antern, fluorescent ligh | t, or cvalume stick | | | |



| Item | Smooth Waters | | Partially smoot | Partially smooth waters | | Beyond partially smooth waters | |
|---|---|---|--|-------------------------------------|--|--------------------------------|--|
| | Requires Registration | Not requiring Registration | Requires Registration | Not requiring Registration | Requires Registration | Not requiring Registration | |
| Navigation Lights when operating petween sunset and sunrise | Required | Required | Required | Required | Required | Required | |
| V Sheet | | | Required | Recommended | Required | Recommended | |
| Flares (two red nand flares and two orange smoke lares | | | Required | Recommended | Required | Recommended | |
| Firefighting | Required | Recommended | Required | Recommended | Required | Recommended | |
| Equipment | A registered tender more than 5m in length must be equipped with firefighting equipment capable of extinguishing a fire of effectively. It is recommended that tenders not requiring registration also carry this equipment | | | | | | |
| EPIRB (406 MHz) | | | | | Required | Required | |
| Navigation (a compass and a navigation chart) | | | Recommended | Recommended | Recommended | Recommended | |
| Anchoring (type | Recommended | Recommended | Recommended | Recommended | Recommended | Recommended | |
| | | if less than 5m if 5m – 6m less than 5m, the cabl | One anchor with at least 27m of cable le can be chain or rope. | | One anchor with at least 27m of cable ched to the anchor and a rope. | | |
| Dumping / bailing | Recommended | Recommended | Recommended | Recommended | Recommended | Recommended | |
| Pumbina / bailina | | | | | | | |
| | | n, a pump or other bail | ing equipment with a n | ninimum capacity of 45L | _ per minute. | | |
| Pumping / bailing equipment Manual propulsion | | n, a pump or other bail Recommended | ing equipment with a n | ninimum capacity of 45L Recommended | per minute. Recommended | Recommended | |
| equipment | For a tender 5m – 6m Recommended | | Recommended | | | | |

